

IRRIGATION PROBE FOR ABLATION DURING OPEN HEART SURGERY

CROSS-REFERENCE TO RELATED APPLICATION

5 This application is a continuation-in-part of U.S. Application No. 09/370,601, filed August 10, 1999, the disclosure of which is incorporated herein by reference.

FIELD OF THE INVENTION

10 The present invention is directed to an irrigation ablation probe for use during open heart surgery.

BACKGROUND OF THE INVENTION

15 Atrial fibrillation is a common sustained cardiac arrhythmia and a major cause of stroke. This condition is perpetuated by reentrant wavelets propagating in an abnormal atrial-tissue substrate. Various approaches have been developed to interrupt wavelets, including surgical or catheter-mediated atriotomy. It is believed that to treat atrial fibrillation by radio-frequency ablation using a catheter, continuous linear lesions must be formed to segment the heart tissue. By segmenting the heart tissue, no electrical activity can be transmitted from one segment to another. Preferably, the segments are made too small to be able to sustain the fibrillatory process.

20 It has been found that over 60% of patients with mitral valve problems also have atrial fibrillation. Moreover, patients undergoing open heart surgery commonly develop atrial fibrillation during the surgery, and thus it would be useful to address this problem during the surgery. Accordingly, under certain circumstances it may be desirable to treat atrial fibrillation during open heart surgery, for example, when a patient is undergoing a mitral valve replacement or repair procedure. Accordingly, a need exists for devices and methods for treating atrial fibrillation during
25 open heart surgery.

SUMMARY OF THE INVENTION

The present invention is directed to an irrigation probe particularly useful for treating atrial fibrillation during open heart surgery. The probe of the present invention is also useful for other ablation and mapping procedures, particularly where irrigation of the ablation site is desired, such as for treating ventricular tachycardia. The invention is also directed to novel methods for treating atrial fibrillation with the probe of the invention. In accordance with the present invention, the probe comprises a rigid probe body and an irrigation electrode, which provides cooling and irrigation in the region of the tissue being ablated.

In one embodiment, the invention is directed to an irrigation ablation probe comprising a generally rigid probe body having proximal and distal ends. The probe body has an electrode at its distal end defining an inner cavity and having at least one irrigation opening through which fluid can pass and means for introducing fluid into the inner cavity. In a preferred embodiment an infusion tube having proximal and distal ends is in fluid communication with the inner cavity. In another preferred embodiment the infusion tube extends through the probe body for introducing fluid into the inner cavity of the electrode. In yet another preferred embodiment the electrode comprises an elongated body having first and second ends, which is fixedly attached, either directly or indirectly, to the distal end of the rigid probe body at a point along the elongated electrode body between its ends, wherein the angle formed between the distal end of the probe body and the electrode is greater than 0° . In still another preferred embodiment the electrode is attached generally perpendicular to the distal end of the rigid probe body and has at least three irrigation openings through which fluid can pass. In still yet another preferred embodiment the electrode comprises a flexible metal ribbon coiled around the outside of a looped irrigation tube fixedly attached, either directly or indirectly, to the distal end of the rigid probe body, where the irrigation tube has irrigation openings through which fluid can pass to the electrode and wherein the spaces between the coils provide openings through which fluid can pass to the outside of the irrigation probe.

In another embodiment, the invention is directed to an irrigation ablation probe. The probe comprises a generally rigid probe body as described above and a handle. The handle is mounted to the proximal end of the probe body. In a preferred embodiment, the generally rigid probe body

comprises a tubular body, an elongated electrode having first and second ends mounted to the distal end of the rigid probe body at a point along the elongated electrode body between its ends, wherein the angle formed between the distal end of the probe body and the electrode is greater than 0° , and a non-conductive sheath covering the length of the probe body. In still yet another embodiment the electrode comprises a flexible metal ribbon coiled around the outside of a looped irrigation tube fixedly attached either directly or indirectly to the distal end of the rigid probe body, where the irrigation tube has irrigation openings through which fluid can pass to the electrode and wherein the space between the coils provide openings through which fluid can pass to the outside of the irrigation probe.

In another preferred embodiment, the generally rigid probe body comprises tubing having proximal and distal ends and at least one lumen extending therethrough. An electrode as described above is mounted at the distal end of the tubing. The electrode has at least one irrigation opening through which fluid can pass. The probe body further comprises means for introducing fluid through the irrigation opening(s) of the electrode and a stiffening wire extending through a lumen of the tubing. A preferred means for introducing fluid comprises an infusion tube that extends through a lumen of the tubing with the distal end of the infusion tube in fluid communication with the one irrigation opening(s) in the electrode. In one embodiment, an elongated electrode having first and second ends is mounted to the distal end of the rigid probe body at a point along the elongated electrode body between its ends, wherein the angle formed between the distal end of the probe body and the electrode is greater than 0° . In a preferred embodiment the electrode is fixedly attached, either directly or indirectly, generally perpendicular to the rigid probe body and has at least three irrigation openings through which fluid can pass. In another preferred embodiment, the electrode comprises a flexible metal ribbon coiled around the outside of a looped irrigation tube fixedly attached either directly or indirectly to the distal end of the rigid probe body, where the irrigation tube has irrigation openings through which fluid can pass to the electrode and wherein the space between the coils provide openings through which fluid can pass to the outside of the irrigation probe.

In still another embodiment, the invention is directed to a method for treating atrial fibrillation in a patient. The method comprises opening the heart of the patient and ablating at least one linear lesion in the heart tissue using an irrigation probe as described above.

5 DESCRIPTION OF THE DRAWINGS

These and other features and advantages of the present invention will be better understood by reference to the following detailed description when considered in conjunction with the accompanying drawings wherein:

FIG. 1 is a side view of an embodiment of an irrigation probe according to the invention.

FIG. 2 is a side cross-sectional view of the handle of the irrigation probe of FIG. 1.

FIG. 3 is a perspective view of the distal end of the T-shaped irrigation probe of FIG. 1.

FIG. 4 is a side view of an alternative embodiment of an irrigation probe according to the invention.

FIG. 5 is a side cross-sectional schematic view of the distal end of the flexible metal ribbon irrigation probe of FIG. 4, wherein the rigid probe body comprises at least one lumen.

FIG. 6 is an end cross-sectional view of the distal end of the flexible metal ribbon irrigation probe of FIG. 4.

FIG. 7 is a side view of an alternative embodiment of an irrigation probe according to the invention.

FIG. 8 is a perspective view of the distal end of the flexible metal ribbon irrigation probe of FIG. 7.

DETAILED DESCRIPTION

The present invention is directed to an irrigation probe for use during open heart surgery. In one embodiment, as shown in FIGs. 1 and 2, the irrigation probe **10** comprises a probe body **12** mounted to a handle **14**. The probe body **12** comprises a tubular body **16**, having proximal and distal ends, covered over by a non-conductive covering or sheath **18** along its length and an electrode **19** mounted at the distal end of the tubular body. The electrode **19** is a generally hollow tubular

structure having two ends **20** and defining an inner cavity therein. The electrode **19** is generally perpendicular to the tubular body **16** and fixedly attached to the tubular body **16** at a point between the two ends **20** of the electrode. The junction of the tubular body **16** and the electrode **19** forms an angle α that is greater than 0° , preferably greater than 10° , more preferably greater than 20° , even more preferably ranging from 70 to 110° , still more preferably ranging from 85 to 95° . Still more preferably the electrode is fixedly attached at an angle α of about 90° relative to the distal end of the probe body, thus forming a generally T-shaped arrangement. The tubular body **16** extends the entire length of the probe body **12**, with the proximal end of the tubular body extending into the handle **14** as described in more detail below. The probe body **12** preferably has a length (from the distal end of the handle to the distal end of the probe body) ranging from about 3.5 inches to about 12 inches, more preferably from about 5 to about 10 inches, still more preferably from about 7 to about 8 inches.

The tubular body **16** and the electrode **19** are both made of a material that is generally rigid so that the probe body **12** cannot bend during ablation, such as, for example, stainless steel (preferably 304VSS) or nitinol. Preferably the tubular body **16** and the electrode **19** have an inner diameter ranging from about 0.40 inch to about 0.80 inch, more preferably about 0.047 inch, and an outer diameter ranging from about 0.50 inch to about 0.90 inch, more preferably about 0.059 inch. If desired, the tubular body **16** and/or the electrode **19** can be heat-treated so that they are malleable enough to be bent by a physician to a desired shape but still rigid enough that they will not bend in use during a procedure. For example, for 304VSS stainless steel, the material is heated to about 800°F with electrical current or in a salt bath. The hollow interior of the tubular body **16** forms a lumen through which saline and the like may be conducted to the inner cavity of the electrode **19** and from there infused during a procedure, as described in more detail below. Alternatively the tubular body **16** could be solid and fluids could be introduced into the inner cavity of the electrode **19** by a separate external tube or the like.

The non-conductive sheath **18** extends from a proximal end inside the handle **14** to a distal end at the union of the tubular body **16** and the electrode **19**. The sheath **18** can be made of any suitable biocompatible non-conductive material, such as polyurethane. In this arrangement, the

electrode 19 is exposed, i.e., not covered by the sheath 18, for ablating tissue, mapping, etc. Preferably the length of the electrode 19 ranges from about 0.50 inch to about 1.5 inches, more preferably from about 0.75 inch to about 1.25 inches.

In the depicted embodiment, the length of the probe body 12 is approximately 7 inches. The proximal section of the probe body 12, i.e., the portion extending from the handle 14, is approximately 5.5 inches. The length of the electrode 19, is approximately 1 inch.

As shown in detail in FIG. 3, the electrode 19 has a series of irrigation openings 21 for passage of a cooling fluid out through the inner cavity of the electrode 19. The irrigation openings 21 can take any suitable shape, such as rectangular or oval slots or round holes. In a preferred embodiment the electrode 19 has at least three irrigation openings 21. The irrigation openings 21 are preferably in the section of the electrode 19 that is to be in contact with the tissue during a procedure, e.g., to enhance the cooling of an ablation site.

Saline or other suitable fluid is introduced into the inner cavity of the electrode 19 through any suitable means. In the embodiment of FIGs. 1 to 3, fluids are introduced into the inner cavity of the electrode 19 via the tubular body 16 through a luer hub 22 or the like at the proximal end of the probe 10. The luer hub 22 is connected to a flexible plastic tubing 24, e.g., made of polyimide. The plastic tubing 24 is attached, either directly or indirectly, to the proximal end of the tubular body 16, preferably within the handle 14, as shown in FIG. 2. Alternatively, the tubing 24 can be connected to a suction source (not shown) to permit aspiration of fluid from the region of tissue being operated on.

As shown in FIG. 2, the handle 14 comprises a housing 26 having a generally open interior 28. The tubular body 16 and sheath 18 extend into the distal end of the handle housing 26. In the depicted embodiment, the sheath 18 terminates a short distance proximal to the distal end of the housing 26. The tubular body 16 continues proximally beyond the sheath 18. The flexible plastic tubing 24 extends into the proximal end of the handle housing 26. The plastic tubing 24 is attached to the tubular body 16 within the open interior 28 of the handle, preferably at a point proximal to the proximal end of the sheath 18. The plastic tubing 24 can be attached to the tubular

body 16 by any suitable means, for example, polyurethane glue. By this design, cooling fluid is introduced through the luer hub 22, through the plastic tubing 24, through the tubular body 16 and out the irrigation openings 21 in the electrode 19.

Alternatively, fluid could be supplied to the electrode 19 and thereby the irrigation openings 21 via a separate irrigation tube (not shown) that can either run external to the tubular body 16 and attach directly to the electrode 19, or can extend through the tubular body 16 to the electrode 19. In either, case this separate irrigation tube could be made of any suitable material, e.g., plastic or metal, and attach to the electrode 19 by any direct or indirect means.

An electrode lead wire 30 having proximal and distal ends is electrically connected at or adjacent its distal end to the probe body 16. The proximal end of the lead wire 30 is attached to a connector 32 for connection to a suitable source of ablation energy, e.g., radio frequency energy, or to an appropriate monitor. In the depicted embodiment, the lead wire 30 extends into the proximal end of the handle housing 26. Within the open interior 28 of the handle 14, the distal end of the lead wire 30 is wrapped around the portion of the tubular body 16 not covered by the sheath 18 and held in place by solder or the like. The portion of the lead wire 30 that extends outside the handle 14 is covered by a flexible plastic protective tubing 34, e.g., made of polyimide.

An alternative embodiment of an irrigation probe according to the invention is shown in FIGs. 4 to 6. As shown in FIG. 4, the probe 10 comprises a probe body 12 and a handle 14. The probe body 12 comprises a non-conductive tubing 40 having proximal and distal ends. In a particularly preferred embodiment, the non-conductive tubing 40 comprises outer and inner plastic walls, e.g., of polyurethane or polyimide, surrounding an imbedded braided mesh of stainless steel or the like. Preferably the tubing has an outer diameter of less than 8 French, more preferably less than 7 French. The tubing 40 has three lumens 42, 44 and 46 extending along its length.

131 The irrigation probe comprises a metal ribbon electrode 47 at the distal end 48 of the non-conducting tube 40 comprising an exposed metallic ribbon 49 that is coiled around a loop of irrigation tubing 56, both of which are indirectly or directly fixedly attached to the distal end 48 of the non-conducting tube 40. As illustrated in FIG. 5, the probe's distal end 48 is generally solid,

having a fluid passage 50 and first and second blind holes 52 and 54 that correspond in size and location to the three lumens 46, 42 and 44, respectively, in the non-conductive tubing 40. In the embodiment shown, the fluid passage 50 is in fluid communication with the inner cavity of the flexible irrigation tube 56, which extends from the distal end of the fluid carrying lumen 46 out of the probe's distal end 48. The irrigation tube 56 has a series of irrigation openings 57 for passage of a cooling fluid out through the spaces between the coils of the metallic ribbon 49, as described in more detail below. The irrigation openings 57 can take any suitable shape, such as rectangular or oval slots or round holes. In a preferred embodiment the irrigation tubing 56 has at least three irrigation openings 57. The irrigation openings 57 are preferably in the section of the irrigation tubing 56 corresponding to the section of the metal ribbon electrode 47 that is to be in contact with the tissue during an ablation procedure to enhance the cooling of the ablation site.

The metallic ribbon 49 is coiled loosely around the irrigation tube 56 such that fluid can pass unimpeded to the outside of the metal ribbon electrode 47. The metal ribbon electrode 47, as shown in detail in FIG. 5, comprises a continuous ribbon 49 of conducting metal, extending outside of the probe's distal end 48 and coiled about the flexible irrigation tube 56 in a loop, having a radius ranging from about 0.5 inch to 1.5 inches. The metal ribbon 49 can be coiled in any manner wherein the coils of the metal ribbon define an inner tubular passage through which the irrigation tube 56 runs and wherein the coils of metal ribbon 49 are generally spaced sufficiently far apart to allow fluid to escape through the irrigation passages. In a preferred embodiment the metal ribbon electrode 49 is coiled around from 1% to 100% of the length of the irrigation tube 56 that is outside the probe body 12. More preferably, the metal ribbon 49 is coiled around from 20% to 80% of the length of the irrigation tube 56, still more preferably the metal ribbon electrode is coiled around from 40% to 60% of the length of the irrigation tube 56. The metal ribbon 49 can be made of any suitable material, and is preferably machined from a .005 inch thick ribbon of nitinol.

The metal ribbon 49 and the irrigation tube 56 can be attached to the probe's distal end 48 in any suitable manner. In the depicted embodiment, the metal ribbon 49 and the irrigation tube 56 are each attached at both ends to the probe's distal end 48 by a polyurethane glue seal 58 or the like.

However, any other means for fixedly mounting the metal ribbon 49 and the irrigation tube 56 on the probe's distal end 48 can also be used. For example, only one end of the metal ribbon 49 and/or the irrigation tube 56 may be attached to the probe's distal end 48.

The metal ribbon electrode 47 is connected to a lead wire 67 having proximal and distal ends. The proximal end of the lead wire 67 for the metal ribbon electrode 47 extends through the third lumen 46 of tubing 40 and through the handle 14. The distal end of the lead wire 67 for the metal ribbon electrode 47 extends through the third lumen 46 and is attached to the metal ribbon electrode 47 by any conventional technique, for example, by soldering.

In the embodiment shown, a mapping ring electrode 62 is mounted on the tubing 40 proximal to the probe's distal end 48. It is understood that the presence and number of ring electrodes may vary as desired. The ring electrode 62 is slid over the tubing 40 and fixed in place by glue or the like. The ring electrode 62 can be made of any suitable material, and is preferably machined from platinum-iridium bar (90% platinum/10% iridium).

The ring electrode 62 is connected to a lead wire 64 having proximal and distal ends. The proximal end of the lead wire 64 for the ring electrode 62 extends through the first lumen 42 of tubing 40 and through the handle 14. The lead wire 64 can be connected to the ring electrode 62 by any conventional technique. Connection of the lead wire 64 to the ring electrode 62 is preferably accomplished by first making a small hole through the tubing 40. Such a hole can be created, for example, by inserting a needle through the tubing 40 and heating the needle sufficiently to form a permanent hole. The lead wire 64 is then drawn through the hole by using a microhook or the like. The ends of the ring electrode lead wire 64 are then stripped of any coating and soldered or welded to the underside of the ring electrode 62, which is then slid into position over the hole and fixed in place with polyurethane glue or the like. Any other means for fixedly mounting the ring electrode 62 to the tubing 40 can also be used.

Both lead wires 64 and 67 terminate at their proximal end in a connector 32 that may be plugged into an appropriate monitor and/or source of radio frequency or other ablation energy. The portion of the lead wires 64 and 67 extending out the proximal end of the handle 14 are enclosed

within a protective tubing 34, which can be made of any suitable material, preferably polyimide, as shown in FIG. 4.

An infusion tube 72 is provided for infusing fluids, e.g., saline, to cool the metal ribbon electrode 47 during ablation. The infusion tube 72 may also be used to infuse drugs to the ablation site. The infusion tube 72 may be made of any suitable material, and is preferably made of polyimide tubing. The infusion tube 72 has proximal and distal ends, with its distal end mounted in the fluid passage 50 of the probe's distal end 48 by any suitable method, e.g., by polyurethane glue or the like. The infusion tube 72 extends from the probe's distal end 48, through the third lumen 46 of the tubing 40, and through the handle 14. As would be recognized by one skilled in the art, the distal end of the infusion tube 72 can be positioned at any point within the third lumen 46. The proximal end of the infusion tube 72 ends in a luer hub 22 or the like. Any other means for infusing fluids to the metal ribbon electrode 47 can also be used, including running the infusion tube 72 external to the tubing 40 and fluid passage 50.

A stiffening wire 74, having proximal and distal ends, is mounted in the second lumen 44 of the tubing 40. The stiffening wire 74 is made of a rigid metal or plastic material, preferably stainless steel, to prevent the probe body 12 from bending during a procedure. If desired, the stiffening wire 74 can be heat-treated so that it is malleable and can be bent to a desired shape before use, but still rigid enough that it will not bend in use during a procedure. A non-conductive tube 76, preferably made of polyimide, is attached to the distal end of the stiffening wire 74 for mounting the stiffening wire in the probe's distal end 48. The non-conductive tube 76 extends out of the second lumen 44 and into the second blind hole 54 in the probe's distal end 48, and is secured in place by polyurethane glue or the like. Any other means for securing the stiffening wire 74 within the probe can also be used. The proximal end of the stiffening wire 74 terminates in the handle 14 or near the proximal end of the probe body 12.

While FIGs. 4 to 6 depict an irrigation probe 10 having a metal ribbon electrode 47, it will be understood that the irrigation probe 10 described above and illustrated in FIGs. 4 to 6 could also house the generally T-shaped electrode 19 illustrated in FIGs. 1 to 3. In this embodiment the

generally T-shaped electrode **19** is fixedly attached, either directly or indirectly, to the probe's distal end **48** such that the fluid passage **50** is in fluid communication with the inner cavity of the generally T-shaped electrode **19**. The construction and function of the lumens **42**, **44**, and **46**, and the remainder of the probe **10** would be similar to that described above and shown in FIGs. 4 to 6.

5 In another embodiment, as shown in FIGs. 7 and 8, the irrigation probe **10** comprises a probe body **12** mounted to a handle **14**, which is described in detail above. The probe body **12** comprises a tubular body **16**, having proximal and distal ends, covered over by a non-conductive covering or sheath **18**. In this embodiment, a metal ribbon electrode **35** comprising a coiled metal ribbon **33** and a loop of flexible irrigation tube **36** is disposed at the distal end of the probe body **12** and fixedly
10 attached, either directly or indirectly, to the distal end of the tubular body **16**. The probe body **12** preferably has a length (from the distal end of the handle to the distal end of the probe body) ranging from about 3.5 inches to about 12 inches, more preferably from about 5 to about 10 inches, still more preferably from about 7 to about 8 inches.

The tubular body **16** is made of a material that is generally rigid so that the probe body **12**
15 cannot bend during ablation, such as, for example, stainless steel (preferably 304VSS) or nitinol. Preferably the tubular body **16** has an inner diameter ranging from about 0.40 inch to about 0.80 inch, more preferably about 0.047 inch, and an outer diameter ranging from about 0.50 inch to about 0.90 inch, more preferably about 0.059 inch. If desired, the tubular body **16** can be heat-treated so that it is malleable enough to be bent by a physician to a desired shape but still rigid enough that it will
20 not bend in use during an ablation procedure. The hollow interior of the tubular body **16** forms a lumen through which saline and the like may be conducted to the irrigation tube **36** of the metal ribbon electrode **35** and from there infused during an ablation procedure, as described in more detail below. Alternatively, the tubular body **16** could be solid, in which case fluids could be introduced into the irrigation tube **36** via a separate external tube or the like.

25 The non-conductive sheath **18** extends from the proximal end of the tubular body **16** inside the handle **14** to the distal end of the tubular body at the union of the tubular body **16** and the metal ribbon electrode **35**. The sheath **18** can be made of any suitable biocompatible non-conductive material, such as polyurethane. Preferably the diameter of the loop of the metal ribbon electrode **35**

ranges from about 0.50 inch to about 1.5 inches, more preferably from about 0.75 inch to about 1.25 inches.

In the depicted embodiment, the length of the probe body 12 is approximately 7 inches. The proximal section of the probe body 12, i.e., the portion extending from the handle 14, is approximately 5.5 inches. The diameter of the loop of the metal ribbon electrode 35 is approximately 1 inch.

As shown in detail in FIG.8, the metal ribbon electrode 35 comprises an irrigation tube 36 having first and second ends 37, at least one of which is fixedly attached either directly or indirectly to the tubular body 16, similar to the embodiment depicted in FIGs. 4 to 6. The irrigation tube 36 is bent so as to form a loop and the metal ribbon 33 is in turn coiled around the irrigation tube 36 and fixedly attached, either directly or indirectly, to the tubular body 16. In one preferred embodiment, the metal ribbon 33 and irrigation tube 36 are both attached to the tubular body 16 at both ends by any direct or indirect means, e.g., via a glue seal 38 as shown above in FIG. 5. Any other means for attaching the metal ribbon 33 and the irrigation tube 36 can also be used.

As shown, the irrigation tube 36 has a series of irrigation openings 39 for passage of a cooling fluid out through the metal ribbon 33. The irrigation openings 39 can take any suitable shape, such as rectangular or oval slots or round holes. In a preferred embodiment, shown in FIG. 8, the irrigation tube 36 has at least three irrigation openings 39. The irrigation openings 39 are preferably in the section of the irrigation tube 36 corresponding to the section of the metal ribbon 33 that is to be in contact with the tissue during a procedure, e.g., to enhance the cooling of the ablation site. The metal ribbon 33 is coiled loosely around the irrigation tube 36 such that fluid can pass unimpeded through the metal ribbon 33.

Saline or other suitable fluid is introduced into the tubular body 16 through a luer hub 22 or the like at the proximal end of the probe 10. The luer hub 22 is connected to a flexible plastic tubing 24, e.g., made of polyimide. The plastic tubing 24 is attached, either directly or indirectly, to the proximal end of the tubular body 16, preferably within the handle 14, as shown in FIG. 7. By this design, cooling fluid is introduced through the luer hub 22, through the plastic tubing 24, through the

tubular body 16, through the first and second ends 37 of the irrigation tube 36 and out the irrigation openings 39.

The irrigation probe shown in various embodiments in FIGs. 1 to 8, having either a metal ribbon electrode or a generally T-shaped electrode, can be used in any manner in which a standard probe can be used. For example, the above described probes can be used during open heart surgery for ablation. During an ablation procedure, the heart is opened and the irrigated electrode is used to form continuous linear lesions by ablation. As used herein, a linear lesion refers to any lesion, whether curved or straight, between two anatomical structures in the heart that is sufficient to block a wavelet, i.e., forms a boundary for the wavelet. Anatomical structures, referred to as "atrial trigger spots", are those regions in the heart having limited or no electrical conductivity and are described in Haissaguerre et al., "Spontaneous Initiation of Atrial Fibrillation by Ectopic Beats Originating in the Pulmonary Veins", New England Journal of Medicine, 339:659-666 (Sept. 3, 1998), the disclosure of which is incorporated herein by reference. The linear lesions typically have a length of from about 1 cm to about 4 cm, but can be longer or shorter as necessary for a particular procedure.

The probe described in FIGs 1 to 3 having a long tubular electrode is particularly useful for this procedure because it can create relatively long lesions. The probe depicted in FIGs. 4 to 6 above, having a smaller but flexible ablation electrode, is useful if the surgeon does not want to ablate as much tissue or wants to ablate a more precise lesion. The above-described probe having a flexible body is particularly useful if the surgeon needs to have a probe that conforms to a particular site to better ablate a desired region of tissue. Additionally, the flexible electrode is particularly useful for ablating locations where it is desirable to have the electrode conform to the tissue, rather than having the tissue conform to the electrode, for example, an atrial appendage. Further, the circular coil design can be used to form a generally circular region around an orifice of a tubular structure, such as a pulmonary vein, the coronary sinus, the superior vena cava, or the inferior vena cava. Once the heart is closed, the surgeon can use the probe on the outside of the heart, not only to ablate, but to verify that the electrical conduction has been stopped using the mapping electrodes. As would be

recognized by one skilled in the art, the probes of the present invention can be used during open heart surgery for other procedures as well.

5 The preceding description has been presented with reference to presently preferred embodiments of the invention. Workers skilled in the art and technology to which this invention pertains will appreciate that alterations and changes in the described structure may be practiced without meaningfully departing from the principal, spirit and scope of this invention.

Accordingly, the foregoing description should not be read as pertaining only to the precise structures described and illustrated in the accompanying drawings, but rather should be read consistent with and as support to the following claims which are to have their fullest and fair scope.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2